

## LD LOAD MODULE RIGGING SYSTEM 4 & 6 STATION SPECIFICATION SHEET

| Model Number | Modules Per System | System Capacity pounds | Pressure Rating Psi. 1* | Load Module Dimensions inches L x W X H | Effective Lift Height inches | Air Requirements SCFM 2* | Control Console 4 Station | Control Console 6 Station |
|--------------|--------------------|------------------------|-------------------------|---|------------------------------|--------------------------|---------------------------|---------------------------|
| 4LD12G       | 4                  | 4,800                  | 15                      | 12.2 x 12.2 x 2.38                      | 1/2                          | 20                       | CC64                      |                           |
| 4LD12GHD     | 4                  | 8,000                  | 25                      | 12.2 x 12.2 x 2.38                      | 5/8                          | 28                       | CC64                      |                           |
| 4LD15G       | 4                  | 8,400                  | 15                      | 15.2 x 15.2 x 2.38                      | 5/8                          | 28                       | CC64                      |                           |
| 4LD15GHD     | 4                  | 14,000                 | 25                      | 15.2 x 15.2 x 2.38                      | 3/4                          | 36                       | CC64                      |                           |
| 4LD18G       | 4                  | 12,000                 | 15                      | 18.2 x 18.2 x 2.38                      | 5/8                          | 44                       | CC64                      |                           |
| 4LD18GHD     | 4                  | 20,000                 | 25                      | 18.2 x 18.2 x 2.38                      | 3/4                          | 64                       | CC64                      |                           |
| 4LD21G       | 4                  | 16,800                 | 15                      | 21.2 x 21.2 x 2.38                      | 3/4                          | 48                       | CC64                      |                           |
| 4LD21GHD     | 4                  | 32,000                 | 29                      | 21.2 x 21.2 x 2.38                      | 1                            | 72                       | CC64                      |                           |
| 4LD24GHD     | 4                  | 40,000                 | 29                      | 24.8 x 24.2 x 2.5                       | 1                            | 92                       | CC64                      |                           |
|              |                    |                        |                         |   |                              |                          |                           |                           |
| 6LD12G       | 6                  | 7,200                  | 15                      | 12.2 x 12.2 x 2.38                      | 1/2                          | 30                       |                           | CC66                      |
| 6LD12GHD     | 6                  | 12,000                 | 25                      | 12.2 x 12.2 x 2.38                      | 5/8                          | 42                       |                           | CC66                      |
| 6LD15G       | 6                  | 12,600                 | 15                      | 15.2 x 15.2 x 2.38                      | 5/8                          | 42                       |                           | CC66                      |
| 6LD15GHD     | 6                  | 21,000                 | 25                      | 15.2 x 15.2 x 2.38                      | 3/4                          | 54                       |                           | CC66                      |
| 6LD18G       | 6                  | 18,000                 | 15                      | 18.2 x 18.2 x 2.38                      | 5/8                          | 66                       |                           | CC66                      |
| 6LD18GHD     | 6                  | 30,000                 | 25                      | 18.2 x 18.2 x 2.38                      | 3/4                          | 96                       |                           | CC66                      |
| 6LD21G       | 6                  | 25,200                 | 15                      | 21.2 x 21.2 x 2.38                      | 3/4                          | 72                       |                           | CC66                      |
| 6LD21GHD     | 6                  | 48,000                 | 29                      | 21.2 x 21.2 x 2.38                      | 1                            | 108                      |                           | CC66                      |
| 6LD24GHD     | 6                  | 60,000                 | 29                      | 24.8 x 24.2 x 2.5                       | 1                            | 138                      |                           | CC66                      |

\*1 pressure At full rated capacity per module

\*2 Values are for smooth sealed concrete, 90 PSIG Min air source, filled expansion joints & cracks. Includes modest safety Factor.